

AMENDMENTS TO THE CLAIMS

1. (Canceled)

2. (Currently Amended) ~~[[A]]~~ The speaker attaching construction according to claim ~~[[1]]~~ 5, where the each said fixture is secured on the speaker frame by tightening a screw in a screw hole formed in the first engager.

3. (Currently Amended) ~~[[A]]~~ The speaker attaching construction, ~~characterized by mounting, on a plate, a speaker removably provided with fixtures, having an engager on one side of an engaging plate and an engager formed with an engaging piece on other side of the engaging plate, at a plurality of points by engaging the engagers with receivers of a speaker frame, through engaging the engaging pieces passed fixing holes of the plate and elastically restored,~~ according to claim 5, wherein at least one of the fixing points ~~being~~ is arranged close to a lower end of the speaker frame, and wherein ~~[[a]]~~ water intruding between the speaker frame and the attaching plate is to be drained outward of the attaching plate through an internal space of the fixture close to the lower end.

4. (Canceled)

5. (Newly Submitted) A speaker construction, comprising:
an attaching plate; and
a speaker assembly to be mounted on said attaching plate,
wherein said speaker assembly comprises:

a speaker removably provided with a plurality of fixtures at a plurality of fixing points mounted on a speaker frame, each said fixture including:
first and second engagers arranged on opposite sides of the attaching plate, each said second engager being formed with an engaging piece; and
a plurality of receivers formed in said speaker frame so as to engage said first engagers,

wherein each said engaging piece is elastically passed through a fixed hole in said attaching plate and is elastically restored after passing through the fixed hole so as to clamp the attaching plate to the speaker frame.

6. (Newly Submitted) The speaker attachment construction according to claim 5, further comprising an adapter arranged between the attaching plate and the speaker frame.

7. (Newly Submitted) The speaker attaching construction according to claim 5,

wherein each said engaging piece has a first slant that is slanted in a spreading manner, a second slat that is slanted in a reducing manner from the top end of the first slant, and a top end face extending horizontally from the top end of the second slant.